

**viva**  
MADE

**aur6**

**aura nero**  
60x60



aura bianco

60x60



aura bianco  
60x60



# aur6


colori e formati - colours and sizes - couleurs et formats - farben und formate - colores y tamaños - цвета и форматы

## BIANCO




**E10H** Bianco Nat. Rett.  
60x60 - 23<sup>5/8</sup>"x23<sup>5/8</sup>" 64 ■

**E6MD** Bianco Antislip Rett.  
60x60 - 23<sup>5/8</sup>"x23<sup>5/8</sup>" 64 ■




**E13K** Bianco Nat. Rett.  
30x60 - 11<sup>13/16</sup>"x23<sup>5/8</sup>" 64 ■


**E1EC** Bianco Antislip Rett.  
30x60 - 11<sup>13/16</sup>"x23<sup>5/8</sup>" 64 ■



**E13P** Bianco Nat. Rett.  
15x60 - 5<sup>7/8</sup>"x23<sup>5/8</sup>" 79B ■



**E13A** Bianco Nat. Rett.  
10x60 - 3<sup>15/16</sup>"x23<sup>5/8</sup>" 79B ■



**E13F** Bianco Nat. Rett.  
5x60 - 1<sup>15/16</sup>"x23<sup>5/8</sup>" 84 ■

## NERO



**E10K** Nero Nat. Rett.  
60x60 - 23<sup>5/8</sup>"x23<sup>5/8</sup>" 64 ■

**E1EH** Nero Antislip Rett.  
60x60 - 23<sup>5/8</sup>"x23<sup>5/8</sup>" 64 ■



**E13N** Nero Nat. Rett.  
30x60 - 11<sup>13/16</sup>"x23<sup>5/8</sup>" 64 ■

**E1EF** Nero Antislip Rett.  
30x60 - 11<sup>13/16</sup>"x23<sup>5/8</sup>" 64 ■



**E13S 9S5T9R** Nero Nat. Rett.  
15x60 - 5<sup>7/8</sup>"x23<sup>5/8</sup>" 79B ■



**E13E 9B5T9R** Nero Nat. Rett.  
10x60 - 3<sup>15/16</sup>"x23<sup>5/8</sup>" 79B ■




**E13J 9E5T9R** Nero Nat. Rett.  
5x60 - 1<sup>15/16</sup>"x23<sup>5/8</sup>" 84 ■

Si consiglia la posa con fuga 2 mm. - Laying with a 2 mm-joint is recommended. - Pose recommandée avec joints de 2 mm.  
Es wird eine Fugenbreite von 2 mm empfohlen. - Se recomienda la colocación con juntas de 2 mm. -

# aur6

pezzi speciali - trims - pieces speciales - formteile - piezas especiales - специальные изделия



BATTISCOPA - SKIRTING

8x60 - 3<sup>1/8</sup>"x23<sup>5/8</sup>"









**E14J** Nero Nat. Rett.

**E14F** Bianco Nat. Rett.


Pcs. Box 20 20 ■

## imballi e pesi - packing and weight - emballages et poids - verpackung und gewicht - embalajes y pesos - упаковка и вес

Formato Size Format Format Tamaño Формат cm	Spessore Thickness Epaisseur Stärke Espesor Толщина mm	Pz. x Mq. Pieces x Sqm Pcs / M <sup>2</sup> Stk. x Qm Pzs x Mc. Шт x Кв.М.	Pz. x Scat. Pieces x Box Pcs / Bte Stk. x Krt. Pzs x Caja Шт x Кор.	Mq. x Scat. Sqm x Box M <sup>2</sup> / Bte Qm x Krt. Mc. x Caja Кв.М. x Кор.	Peso x Scat. Weight x Box Poids / Bte Gewicht x Krt. Peso x Caja Вес x Кор. Kg	Scat. x Pal. Boxes x Pal. Bte / Pal. Krt. x Pal. Cajas x Pal. Кор. x Подд.	Mq. x Pal. Sqm x Pal. M <sup>2</sup> / Pal. Qm x Pal. Mc. x Pal. Кв.М x Подд.	Peso x Pal. Weight x Pal. Poids / Pal. Gewicht x Pal. Peso x Pal. Вес x Подд. Kg
60x60 Naturale /Antislip	10	2,78	3	1,080	25,00	40	43,20	1000
30x60 Naturale /Antislip	10	5,56	6	1,080	25,00	40	43,20	1000
15x60 Naturale	10	11,11	12	1,080	25,00	50	54,00	1250
10x60 Naturale	10	16,67	12	0,720	16,70	60	43,20	1002
5x60 Naturale	10	33,33	24	0,720	16,70	60	43,20	1002

CARATTERISTICHE TECNICHE Technical Features - Caracteristiques Techniques Technische Eigenschaften - Caracteristicas Tecnicas - Технические Характеристики	NORMA Standard - Norme Norm - Norma - Norma	VALORI Value - Valeur Vorgabe - Valor - Средние
	UNI EN ISO 10545/2	± 0,26% / ± 1,5mm
 <b>PLANARITÀ</b> Flatness - Planéité - Ebenflächigkeit - Planiyud - Плоскостность	ASTM C485 Warpage	
	Calibrated ± 0,75% (max ± 0,09 in)	-
	Rectified ± 0,40% (max ± 0,05 in-size ≤ 60cm) (max ± 0,07 in-size > 60cm)	± 0,25% (max ± 0,05 in-size ≤ 60cm) (max ± 0,07 in-size > 60cm)
 <b>ASSORBIMENTO D'ACQUA - Valore medio in %</b> Water absorption - Average value expressed in % Absorption d'eau - Valeur moyenne en % Wasseraufnahme - Durchschnittswert in % Absorción de agua - Valor medio en % - Поглощение воды	UNI EN ISO 10545/3 ≤ 0,5 % ASTM C373	Conforme Compliant
 <b>RESISTENZA ALLA FLESSIONE</b> Modulus of rupture - Resistance a la flexion Biegefestigkeit - Resistencia a la flexion - Прочность на изгиб	UNI EN ISO 10545/4	≥ 50 N/mm <sup>2</sup>
 <b>FORZA DI ROTTURA</b> Breaking strength - Résistance à la rupture Bruchlast - Resistencia a la rotura - Разрывное усилие	UNI EN ISO 10545/4 ASTM C648	≥ 2000 N 700 LBS
 <b>RESISTENZA AL GELO</b> Frost resistance - Résistance au gel - Frostbeständigkeit Resistencia a las heladas - Морозостойкость	UNI EN ISO 10545/12 ASTM C1026	Conforme Unaffected
 <b>RESISTENZA CHIMICA ad alte e basse concentrazioni di acidi e basi</b> Chemical resistance to high and low acid and basic concentrations Résistance chimique aux hautes et basses concentrations d'acides et de bases Chemikalienfestigkeit bei hohen und niedrigen Konzentrationen von Säuren und Basen Resistencia química con concentraciones altas y bajas de ácidos y bases Химическая стойкость к высоким и низким концентрациям кислот и щелочей	UNI EN ISO 10545/13 ASTM C-650	GA - GLA Unaffected
 <b>RESISTENZA ALLE MACCHIE</b> Stain resistance - Résistance aux taches - Fleckenbeständigkeit Resistencia a las manchas - Стойкость к образованию пятен	UNI EN ISO 10545/14 CTI 81-7D	5 No Evident Variation
 <b>COEFFICIENTE DI ATTRITO</b> Slip resistance - Coefficient de glissement - Rutschfestigkeit Barfußbereich Coeficiente de atrito medio - Коэффициент трения	N 51130 DIN 51097 ANSI A 137.1 - 2012 DCOF ( Section 9.6 ) B.C.R.A.	NATURALE R10 A ANTISLIP R11 B (A+B) Dry ≥ 0,42/Wet ≥ 0,42 Dry ≥ 0,42/Wet ≥ 0,42 ≥ 0,40 ≥ 0,40

Per maggiori chiarimenti sui dati tecnici e sulla garanzia consultare il catalogo generale in vigore. - For further information on technical specifications, please consult our up-dated general catalogue. - Pour toutes informations supplémentaires sur les données techniques et sur les garanties, veuillez consulter le catalogue general en vigueur. - Für weitere Informationen über technische Daten und Garantie beziehen sie sich bitte auf den aktuellen Gesamtkatalog. - Para posteriores informaciones sobre los datos técnicos y la garantía, vease el catalogo general en vigor. - Более подробную информацию о технических данных и гарантии смотрите в действующем сводном катал.





Viva Made is a brand of Emilceramica S.r.l. a socio unico	Sede commerciale/amministrativa
<a href="http://emilgroup.it/viva">emilgroup.it/viva</a> <a href="http://emilgroup.it">emilgroup.it</a>	Via Ghiarola Nuova, 29 - 41042 Fiorano Modenese (Mo) - Italy T +39 0536 835111 - <a href="mailto:info@emilceramicagroup.it">info@emilceramicagroup.it</a> F (Italy) +39 0536 835958 - (Export) +39 0536 835490

